



ISO-9001 Registered Quality System.  
ISO-21469 Compliant.

**Sales, Service & Distribution Center**

Newark, NJ 07105

Phone: 973-589-9150 Fax: 973-589-4432

**Manufacturing, Sales, Service & Distribution Center**

Toledo, OH 43605

Phone: 419-691-2491 Fax: 419-693-3806

**Sales and Tech Service Support**

Phone: 1-800-733-4755

**LUBRIPLATE No's. 130-A & 130-AA**

LUBRIPLATE No's. 130-A & 130-AA are designed for those applications where a grease-type lubricant possessing extremely good water repellency and superior lubrication characteristics are desired. These products are recommended for plain bearings, cams, guides, open gears, slides and chassis lubrication and where temperatures do not exceed 170°F.

**Typical Tests**

	<b><u>No. 130-A</u></b>	<b><u>No. 130-AA</u></b>
Type of Base	Calcium	Calcium
Worked Penetration @ 77°F	235/260	310/340
NLGI No.	2.5	1
ASTM Melting Point	200°F/93°C	190°F/88°C
Mineral Oil Viscosity		
SUS @ 100°F	750	750
cSt @ 40°C	135	135
Color & Character	Beige/Smooth	Beige/Smooth

**Part Numbers**

<b><u>Packaging Available</u></b>	<b><u>No. 130-A</u></b>	<b><u>No. 130-AA</u></b>
Carton, 24/14 oz. Cans	L0043-001	L0044-001
Carton, 6/6 lb. Cans	L0043-006	L0044-006
35 lb. Pail	L0043-035	L0044-035
120 lb., Quarter Size, Drum	-----	L0044-039
420 lb., Full Size, Drum	L0043-040	L0044-040
Carton, 36/1-3/4 oz. Tubes (1x6)	-----	L0044-086
Carton, 36/10 oz. Plastic Tubes	-----	L0044-092