



ISO-9001 Registered Quality System.
ISO-21469 Compliant.

Sales, Service & Distribution Center

Newark, NJ 07105

Phone: 973-589-9150 Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center

Toledo, OH 43605

Phone: 419-691-2491 Fax: 419-693-3806

Sales and Tech Service Support

Phone: 1-800-733-4755

LUBRIPLATE No. 405 CUTTING OIL

(Heavy-Duty Dark Cutting Oil)

LUBRIPLATE No. 405 Cutting Oil is especially recommended for use on low or high carbon steels, alloys and stainless steels where difficult conditions of service are encountered. The unusually high extreme pressure content of this active sulfur product provides optimum results in prolonged tool life, improved finish, more accurate cuts, greater production and reduced labor cost. Not recommended for brass, bronze, copper or aluminum. It is an outstanding dark pipe threading oil.

Typical Characteristics:

Viscosity @ 100°F., SUS/cSt	225/48
Flash Point °F/°C	380/193
Fire Point °F/°C	400/204
API Gravity	25.7
Sulfur	Yes
Active Sulfur	Yes
Chlorine	Yes
Fatty Material	Yes
Color	Dark Brown

LUBRIPLATE No. 405 Cutting Oil is available in the following:

<u>Packaging Available</u>	<u>Part Number</u>
Ctn. 4/1 gallon jugs	L0587-057
5 gallon pail	L0587-060
16 gallon drum	L0587-061
55 gallon drum	L0587-062