ISO-9001 Registered Quality System. ISO-21469 Compliant. Sales, Service & Distribution Center Newark, NJ 07105 Phone: 973-589-9150 Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center Toledo, OH 43605 Phone: 419-691-2491 Fax: 419-693-3806

Sales and Tech Service Support Phone: 1-800-733-4755

LUBRIPLATE BAR AND CHAIN OIL

LUBRIPLATE Bar and Chain Oil is a unique blend of the finest refined petroleum stocks and additives available, designed to provide the chain saw owner with the maximum protection against bar and chain wear. LUBRIPLATE Bar and Chain Oil may safely be used in all makes of chain saws on the market today as a bar and chain lubricant.

COMPARE THESE FEATURES AGAINST ANY OF THE LEADING BAR AND CHAIN OILS ON THE MARKET TODAY:

LUBRIPLATE Bar and Chain Oil:

GREATLY REDUCES BAR BURNING AND CHAIN WEAR -- HAS EXCELLENT PENETRATING AND EXTREME PRESSURE PROPERTIES . . . more than pays for itself in savings through reduced fuel consumption and replacement parts!

FEEDS EVENLY AND PRECISELY . . . one grade for year-round use . . . no need to change oil with temperature changes!

POSSESSES EXCELLENT RESISTANCE TO "THROW-OFF" . . . conditions and protects chain pins and bushings against rust while not contributing to dust-to-dust load-up!

IS NON-GUMMING . . . assures top operating performance of your chain saws, month in and month out!

ADHERES BETTER . . . requires less frequent lubrication intervals in manually operated bar and chain lubricators!

CUTTING CHAIN OPERATES COOLER . . . protects cutting teeth . . . teeth remain sharper longer!

PROTECT THE INVESTMENT YOU HAVE MADE IN YOUR CHAIN SAW....USE ONLY LUBRIPLATE BAR AND CHAIN OIL!

Typical Tests

Viscosity SUS @ 100°F cSt @ 40°C	347 67
Viscosity SUS @ 210°F	53
cSt @ 100°C	8
Flash Point °F/°C Fire Point °F/°C	395/202 430/221
Pour Point °F/°C	-30/-34
SAE Grade	20
Color	L-3

LUBRIPLATE Bar & Chain Oil is available in the following:

Packaging Available	<u>Part No.</u>
Carton, 12/1-quart plastic bottles Carton, 4/1 gallon jugs	L0720-054 L0720-057
55 gallon drum	L0720-062

Printed in USA Revised 5/5/08