



ISO-9001 Registered Quality System.  
ISO-21469 Compliant.

**Sales, Service & Distribution Center**

Newark, NJ 07105  
Phone: 973-589-9150 Fax: 973-589-4432

**Manufacturing, Sales, Service & Distribution Center**

Toledo, OH 43605  
Phone: 419-691-2491 Fax: 419-693-3806

**Sales and Tech Service Support**

Phone: 1-800-733-4755

**LUBRIPLATE AIR TOOL LUBRICANT**

LUBRIPLATE Air Tool Lubricant is an air tool oil that provides excellent lubrication for both rotary and reciprocating types of air tools, such as chipping hammers, impact wrenches, air motors, grinders, reamers, drills, etc. It can be fed through an air line lubricator or by a squirt can directly into the tool through the quick coupling air connection. LUBRIPLATE Air Tool Lubricant provides not only superior lubrication, but dissolves and prevents the formation of gum and varnish deposits so often associated with air tool operations.

For the utmost in safe, simple and economical lubrication of rotary and reciprocating types of air tools, small amounts of LUBRIPLATE Air Tool Lubricant, used on a daily basis, will effectively lubricate the air tool, keeping it clean and free-running.

LUBRIPLATE Air Tool Lubricant, as an air line lubricant, has been used very effectively on the lift cylinders of can fillers in breweries, bottling plants and canning plants, keeping the cylinders clean and eliminating hand cleaning.

**Typical tests on LUBRIPLATE Air Tool Lubricant are as follows:**

Viscosity SUS @ 100°F	-	147
cSt @ 40°C	-	30
Viscosity SUS @ 210°F	-	44
cSt @ 100°C	-	5
Viscosity Index	-	120
ISO Grade	-	32
Flash Point	-	385°F/196°C
Aniline Point	-	200°F/93°C
API Gravity	-	27.4
Pour Point	-	-30°F/-34°C

**LUBRIPLATE Air Tool Lubricant is available in the following:**

<b><u>Packaging Available</u></b>	<b><u>Part No.</u></b>
Carton 12/1 qt. Plastic Jugs	L0713-054
Carton 4/1 Gallon Jugs	L0713-057
5 Gallon pail	L0713-060
16 Gallon Drum	L0713-061
55 Gallon Drum	L0713-062