



ISO-9001 Registered Quality System.
ISO-21469 Compliant.

Sales, Service & Distribution Center
Newark, NJ 07105
Phone: 973-589-9150 Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center
Toledo, OH 43605
Phone: 419-691-2491 Fax: 419-693-3806

Sales and Tech Service Support
Phone: 1-800-733-4755

LUBRIPLATE 981 Natural Gas Compressor Lubricant

Description:

LUBRIPLATE 981 is a synthetic-based lubricant formulated for use in hyper-compressors and natural gas reinjection applications. It features higher film strength than traditional lubricants, protects against corrosion, is fully compatible with most compressor components and minimizes the effect of H2S concentration in sour gas.

Intended Use:

LUBRIPLATE 981 is intended for the lubrication of flooded rotary screw and vane type compressors. LUBRIPLATE 981 may be used as a lubricant for processing natural gas, carbon dioxide and other gases that require an ISO-100 viscosity grade.

Typical Tests:

Viscosity cSt @ 40°C	84.4
Viscosity cSt @ 100°C	16.5
Viscosity Index	218
Pour Point, °C	-45
Flash Point, COC, °C	275
Specific Gravity, 60°F	1.042
Copper Strip 24 hrs/212°F	1b

Packaging Available

55-Gallon Drum

Part Number

L1009-062