



ISO-9001 Registered Quality System.
ISO-21469 Compliant.

Sales, Service & Distribution Center
Newark, NJ 07105
Phone: 973-589-9150 Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center
Toledo, OH 43605
Phone: 419-691-2491 Fax: 419-693-3806

Sales and Tech Service Support
Phone: 1-800-733-4755

LUBRIPLATE 989 Synthetic Compressor Lubricant

Description:

LUBRIPLATE 989 is a synthetic lubricant formulated for use in process gas compression applications that require wide operating temperature ranges and minimum interaction between the lubricant and the process gas.

Intended Use:

LUBRIPLATE 989 is intended for the lubrication of flooded rotary screw and vane-type compressors processing natural gas, carbon dioxide or other hydrocarbon gases. LUBRIPLATE 989 may also be used as a cylinder lubricant for reciprocating compressors processing natural gas, carbon dioxide and other gases that require chemical resistance in an ISO 150 viscosity grade.

Typical Tests:

Viscosity cSt @ 40°C	138
Viscosity cSt @ 100°C	24.4
Viscosity Index	224
Pour Point, °C	-42
Flash Point, COC, °C	245
Fire Point, °C	270
Specific Gravity, 60°F	1.052
Copper Strip Corrosion	1b

Packaging Available

5-Gallon Pail
55-Gallon Drum

Part Number

L1010-060
L1010-062