

# Krytox<sup>®</sup> Sodium Nitrite Inhibited PFPE/PTFE Greases (GPL 22(X) Series)

Version 3.0

Revision Date 02/05/2013

Ref. 15000001171

This SDS adheres to the standards and regulatory requirements of the United States and may not meet the regulatory requirements in other countries.

### SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name Product Grade/Type	::	Krytox <sup>®</sup> Sodium Nitrite Inhibited PFPE/PTFE Greases (GPL 22(X) Series) GPL: 220, 221, 222, 223, 224, 225, 226, 227, 227-500 XHT - AC, ACX, NDR 1466 FG: 30, 32, 34, 35, 36 Corrugator: 226 FG, 227 FG Hi Temp T8-26, T8-27 HTC: 26, 27 AUT 2245 Krytox SLB 266 Krytox MF440
MSDS Number	:	15000001171
Product Use	:	Lubricant
Manufacturer	:	DuPont 1007 Market Street Wilmington, DE 19898
Product Information Medical Emergency Transport Emergency	:	1-800-441-7515 (outside the U.S. 1-302-774-1000) 1-800-441-3637 (outside the U.S. 1-302-774-1139) CHEMTREC: 1-800-424-9300 (outside the U.S. 1-703-527-3887)
Other information	:	professional use

### SECTION 2. HAZARDS IDENTIFICATION

**Emergency Overview** 

The thermal decomposition vapours of fluorinated polymers may cause polymer fume fever with flu-like symptoms in humans, especially when smoking contaminated tobacco. Repeated episodes of polymer fume fever may result in persistent lung effects.

Potential Health Effects Skin

: May cause: slight irritation, Redness.

Material Safety Data Sheet Krytox<sup>®</sup> Sodium Nitrite Inhibited PFPE/PTFE Greases (GPL 22(X) Series) Version 3.0 Revision Date 02/05/2013 Ref. 15000001171 Eyes : May cause eye irritation. Discomfort, tearing, Blurred vision. Repeated exposure Sodium nitrite : May cause heritable genetic damage. Adverse effects from repeated ingestion may include: Reduction of blood's oxygen-carrying capacity, which could produce shortness of breath, headache, fatigue, sweating, confusion, abnormal bluish colour of skin or mucous membranes (cyanosis). Carcinogenicity None of the components present in this material at concentrations equal to or greater than 0.1% are listed by IARC, NTP, or OSHA, as a carcinogen. SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS CAS-No. Component Concentration Perfluoropolyether 71 - 80 % PTFE 18 - 27 % Sodium nitrite 7632-00-0 2% SECTION 4. FIRST AID MEASURES Skin contact : Wash with water and soap as a precaution. : Rinse with plenty of water. If eye irritation persists, consult a specialist. Eye contact 2/8



# Krytox<sup>®</sup> Sodium Nitrite Inhibited PFPE/PTFE Greases (GPL 22(X) Series)

Version 3.0

Revision Date 02/05/2013	Ref. 15000001171
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion.
Ingestion	: Never give anything by mouth to an unconscious person. DO NOT induce vomiting unless directed to do so by a physician or poison control center.
General advice	: When symptoms persist or in all cases of doubt seek medical advice.
SECTION 5. FIREFIGHTING MEAS	SURES
Flammable Properties Flash point	: closed cup does not flash
Thermal decomposition	: 300 ℃ (572 °F)
Fire and Explosion Hazard	: In fire conditions, toxic decomposition products may be formed. (see also section 10)
Suitable extinguishing media	: The product itself does not burn.
	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Firefighting Instructions	: Wear self-contained breathing apparatus (SCBA). Wear suitable protective equipment. Standard procedure for chemical fires.
SECTION 6. ACCIDENTAL RELEA	
	G MEASURES and HANDLING (PERSONNEL) sections before proceeding with clean- L PROTECTIVE EQUIPMENT during clean-up.
Spill Cleanup	: Shovel into suitable container for disposal.
Accidental Release Measures	: Prevent material from entering sewers, waterways, or low areas.
	3 / 8

Material Safety Data Sheet Krytox<sup>®</sup> Sodium Nitrite Inhibited PFPE/PTFE Greases (GPL 22(X) Series) Version 3.0 Revision Date 02/05/2013 Ref. 15000001171 SECTION 7. HANDLING AND STORAGE Handling (Personnel) : Avoid breathing vapors from overheated material. Do not store or consume food, drink or tobacco in areas where they may become contaminated with this material. General industrial hygiene practice. : No special storage conditions required. Keep container closed to prevent Storage contamination. No decomposition if stored and applied as directed. SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION Engineering controls : In the event that the polymer is heated above  $260 \,^{\circ}{\rm C}$  (500  $^{\circ}{\rm F}$ ), local ventilation should be used to avoid exposure to fumes. Personal protective equipment Respiratory protection : No personal respiratory protective equipment normally required. In the case of hazardous fumes caused by overheating, wear self-contained breathing apparatus. : Additional protection: No particular glove type is recommended, but nitrile Hand protection may used. Eye protection : Safety glasses Skin and body protection : No PPE is specified however, avoid contact with skin, eyes, and clothing. Preventive skin protection **Exposure Guidelines** Exposure Limit Values None established. 4/8



# Krytox<sup>®</sup> Sodium Nitrite Inhibited PFPE/PTFE Greases (GPL 22(X) Series)

Version 3.0

Revision Date 02/05/2013

Ref. 15000001171

### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

- Form Color Odor pН
- : grease : white : none : neutral pH: neutralMelting point/range: 320 ℃ (608 ℉)Specific gravity: 1.89 - 1.93 at 24 ℃ (75 ℉)Water solubility: insoluble

# SECTION 10. STABILITY AND REACTIVITY

Stability	: Stable under recommended storage conditions.	
Conditions to avoid	: Decomposition temperature 260 °C (500 °F)	
Hazardous decompo products	ion : Hazardous thermal decomposition products:: Flu	orinated compounds

### SECTION 11. TOXICOLOGICAL INFORMATION

Krytox<sup>®</sup> Sodium Nitrite Inhibited PFPE/PTFE Greases (GPL 22(X) Series)

	Oral ALD	:	> 11,000 mg/kg , rat
	Oral LD50	:	> 5,000 mg/kg , rat
	Skin irritation	:	slight irritation, rabbit
	Eye irritation	:	slight irritation, rabbit
	Sensitisation	:	Animal test did not cause sensitization by skin contact., guinea pig
Perfluoropo	Inhalation 4 h ALC - Approximate Lethal Concentration		ca. > 19.54 mg/l , rat
	Mutagenicity	•	Did not cause genetic damage in cultured bacterial cells.
	Further information	:	The substance is a polymer and is not expected to produce toxic
			5/8



# Krytox<sup>®</sup> Sodium Nitrite Inhibited PFPE/PTFE Greases (GPL 22(X) Series)

Version 3.0

Revision Date 02/05/2013

Ref. 150000001171

PTFE Sodium nitr	Further information : ite Inhalation 4 h LC50 : Mutagenicity :	effects. The substance is a polymer and is not expected to produce toxic effects. 1.45 mg/l , rat Dust Experiments showed mutagenic effects in cultured bacterial cells. Genetic damage in cultured mammalian cells was observed in some laboratory tests but not in others.
	Teratogenicity :	Genetic damage in animals was observed in some laboratory tests but not in others. Animal testing showed effects on embryo-foetal development at levels below those causing maternal toxicity.
SECTION 1	12. ECOLOGICAL INFORMATIO	Ν
Aquat Perfluoropo	ic Toxicity olyether 96 h LC50 :	Oncorhynchus mykiss (rainbow trout) > 1,000 mg/l The substance is a polymer and is not expected to produce toxic effects.
	48 h EC50 :	Daphnia magna (Water flea) > 1,000 mg/l

PTFE

		effects.
Sodium nitrite		
96 h LC50	:	Oncorhynchus mykiss (rainbow trout) 0.54 mg/l
72 h ErC50	:	Desmodesmus subspicatus (green algae) > 100 mg/l
72 h NOEC	:	Desmodesmus subspicatus (green algae) 100 mg/l

48 h EC50

6/8

: Daphnia magna (Water flea) 15.4 mg/l

: The substance is a polymer and is not expected to produce toxic

Material Safety Data Sheet	QUPOND				
Krutov <sup>®</sup> Sodium Nitrite	Inhibited PFPE/PTFE Greases (GPL 22(X) Series)				
Version 3.0					
Version 3.0					
Revision Date 02/05/2013	Ref. 15000001171				
29 d	: NOEC Cyprinus carpio (Carp) 21 mg/l				
Environmental Fate					
Krytox <sup>®</sup> Sodium Nitrite Inhi	bited PFPE/PTFE Greases (GPL 22(X) Series)				
	: Not readily biodegradable.				
Additional ecological informati	ion : No data is available on the product itself.				
SECTION 13. DISPOSAL CONSIL	DERATIONS				
Waste Disposal	: In accordance with local and national regulations.				
Environmental Hazards	: Dispose of container properly.				
EIIVIIUIIIIIeiildi Hazaius	If recycling is not practicable, dispose of in compliance with local regulations.				
SECTION 14. TRANSPORT INFO	RMATION				
Not classified as dangerous ir	the meaning of transport regulations.				
SECTION 15. REGULATORY INF	ORMATION				
TSCA	: On the inventory, or in compliance with the inventory				
SARA 313 Regulated	: Sodium nitrite				
Chemical(s)					
CERCLA Reportable	: 2,000 lbs				
Quantity	Based on the percentage composition of this chemical in the product.: Sodium nitrite				
	Socium minite				
7/8					



# Krytox<sup>®</sup> Sodium Nitrite Inhibited PFPE/PTFE Greases (GPL 22(X) Series)

#### Version 3.0

Revision Date 02/05/2013

Ref. 15000001171

## **SECTION 16. OTHER INFORMATION**

Restrictions for use : Do not use DuPont materials in medical applications involving implantation in the human body or contact with internal body fluids or tissues unless the material has been provided from DuPont under a written contract that is consistent with DuPont policy regarding medical applications and expressly acknowledges the contemplated use. For further information, please contact your DuPont representative. You may also request a copy of the DuPont POLICY Regarding Medical Applications H-50103-3 and DuPont CAUTION Regarding Medical Applications H-50102-3.

Krytox<sup>®</sup> and The DuPont Oval Logo<sup>®</sup> are trademarks of E. I. du Pont de Nemours and Company

Contact person : MSDS Coordinator, DuPont Chemicals and Fluoroproducts, Wilmington, DE 19898, (800) 441-7515

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Significant change from previous version is denoted with a double bar.