



NEX^T GENERATION

SYNTHETIC

GREASES

FOR MAXIMUM
BEARING
PROTECTION

SYNXTREME HD SERIES GREASES

If you're still using conventional petroleum-based greases, you're missing out on the many benefits of Lubriplate SynXtreme Synthetic Greases. They provide a level of performance and versatility we could only dream about just a few years ago. Engineered to provide superior performance throughout a wide range of applications and conditions, these super multi-purpose greases can help you significantly reduce, consolidate and simplify your grease inventory. In fact, they may be the only greases you'll ever need.

100% Synthetic Ultra High-Performance, Calcium Sulfonate Complex Formula.

-45°F to 450°F Effective Operating Lubrication Temperature Ranges.

3X Better Shear Stability and Oxidation, Resistance for Long Lubricant Life.



Lubriplate
Lubricants

Newark, NJ 07105 / Toledo, OH 43605 / 800-733-4755
www.lubriplate.com / LubeXpert@lubriplate.com



Backed By:



Extra Services Package

Plant Surveys / Tech Support / Training
Color Coded Lube Charts & Machine Tags
Lubrication Software / Follow-Up Oil Analysis

Lubriplate® SynXtreme HD Series Greases

SYNXTREME HD-Series:

Extreme-Duty, Multi-Purpose, High-Temperature, Synthetic, Calcium Sulfonate Complex Greases.

These high performance, extreme-duty, multi-purpose, synthetic, calcium sulfonate complex greases provide unsurpassed anti-wear, and extreme pressure protection. They are highly water resistant and work well over a wide range of temperature extremes and other adverse conditions. Superior shear stability and oxidation resistance provide long lasting protection. Available in 3 NLGI grades for a wide range of applications. SYNXTREME HD-2 is NLGI GC-LB certified for wheel bearing and chassis lubrication. SYNXTREME HD-1/220 and HD-2/220 are formulated with a heavier (ISO 220 Grade) base fluid and are recommended for slow to medium speed bearings and other equipment operating under high temperature conditions.



Specifications

LUBRIPLATE PRODUCT	NLGI DENSITY	OIL VIS. cSt / SUS @ 40°C / 100°F	WORKED PENETRATION	RECOMMENDED OPERATING TEMPERATURE RANGE	AW / EP	RUST & OXID. ADDITIVES	WATER RESISTANT
SYNXTREME HD-0	0	100 / 500	355 / 385	-45°F / -43°C to 390°F / 199°C	AW/EP	YES	YES
SYNXTREME HD-1	1	100 / 500	310 / 340	-45°F / -43°C to 440°F / 227°C	AW/EP	YES	YES
SYNXTREME HD-2	2	100 / 500	265 / 295	-45°F / -43°C to 450°F / 232°C	AW/EP	YES	YES
SYNXTREME HD-1/220	1	220 / 1020	310 / 340	-40°F / -40°C to 440°F / 227°C	AW/EP	YES	YES
SYNXTREME HD-2/220	2	220 / 1020	265 / 295	-40°F / -40°C to 450°F / 232°C	AW/EP	YES	YES

Packaging Availability / Part Number

Package / Part Number	Cartridges 14.5 oz / 411g	Pail 35 lb / 19.9 kg	1/4 Drum 120 lb / 54 kg	Drum 420 lb / 191 kg
SYNXTREME HD-0	-	L0403-035	L0403-039	L0403-040
SYNXTREME HD-1	L0402-098	L0402-035	L0402-039	L0402-040
SYNXTREME HD-2	L0401-098	L0401-035	L0401-039	L0401-040
SYNXTREME HD-1/220	L0313-098	L0313-035	L0313-039	L0313-040
SYNXTREME HD-2/220	L0312-098	L0312-035	L0312-039	L0312-040



Lubriplate®
Lubricants

Newark, NJ 07105 / Toledo, OH 43605 / 800-733-4755
www.lubriplate.com / LubeXpert@lubriplate.com



Backed By:



Extra Services Package

Plant Surveys / Tech Support / Training
Color Coded Lube Charts & Machine Tags
Lubrication Software / Follow-Up Oil Analysis